



Product Features

- For removal of chlorine, taste, odour, sediment, rust and scale from drinking water as well as ingredient water for food and beverage facilities
- 5-micron nominal pre-filter extends filter life
- Coconut shell granular carbon used with strong adsorbing pore structure for the treatment of chlorine and other organics
- Rigid construction eliminates sediment unloading and yields a low pressure drop
- Optional 10583-032 spacer allows for cartridge stacking to maximize water throughput for higher-flow applications
- All materials are FDA compliant, under CFR, chapter 21. Certified compliant with NSF International Standard 42

Product Specifications

Dimensions:

Outside diameter: 3" (76 mm)
 Length: 9-7/8" (250.8 mm)

Operating Parameters

Maximum Operating Temperature:
 100°F (38°C)

Recommended Change-Out:

18 000 US gallons of city water per cartridge

Retention Ratings:

5-micron nominal pre filter

Recommended Flow Rate:

2-3 US gallons per minute

Granular Carbon Specifications

Iodine Number, mg/g	850 (min)
Ash, wt%	1.0 (max)
Zinc	0.0 (max)
Density (Apparent), g/cc	0.48 (max)
Heavy Metals, mg/kg	10 (max)
12 US Mesh (170 mm), wt%	5.0 (max)
< 40 US Mesh (0.425 mm), wt%	4.0 (max)

CANADA WEST

3247 Roper Road NW
 Edmonton, AB T6P 0G1
 1-877-456-5760
saleswc@vytal.ca
www.vytal.ca

CANADA EAST

441 Applewood Crescent
 Concord, ON L4K 4J3
 1-888-233-1969
salesec@vytal.ca
www.vytal.ca

USA

345 E Tulare Ave
 Visalia, CA 93277
 1-424-222-7619
saleswusa@vytalusa.com
www.vytalusa.com